



## COMPGUARD DL 6



Date of issue: 13.04.2015

**COMPGUARD DL 6** is a fully synthetic compressor oil.

### Special properties

- High resistance towards oxidation and high temperatures
- Very good corrosion protection
- Very high ageing stability
- No oil change after 500 operation hours necessary

Product Characteristics	Value	Dimension	Norm / Standard
Colour	amber coloured		
Density at 20°C	0,88	g/cm <sup>3</sup>	DIN 51757
Oil type	SHC, ester		
Kinematic viscosity at 40°C	45,6	mm <sup>2</sup> /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	7,4	mm <sup>2</sup> /s	DIN EN ISO 3104
Viscosity index (VI)	126		DIN ISO 2909

### Application

**COMPGUARD DL 6** is especially suitable for the use in rotary piston compressors. There discharge temperatures of up to 180°C can be achieved.

When used in screw compressors, discharge temperatures of up to 280°C can be achieved.

The oil change periods can be extended up to 16 000 operation hours.

### Packaging units

5 l canister, 20 l canister

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>