



COMPGUARD MT 68



Date of issue: 02.10.2017

COMPGUARD MT 68 is a fully synthetic compressor oil with excellent lubricating properties.

Special properties

- High load carrying capacity
- Very good corrosion protection
- Neutral towards elastomers and plastics
- Very good wear protection
- Very high ageing stability

| Product Characteristics | Value | Dimension | Norm / Standard |
|------------------------------|------------------------|--------------------|-----------------|
| Colour | colourless | | |
| Density at 20°C | 0,83 | g/cm ³ | DIN 51757 |
| Operating temperature range | to 160 | °C | |
| Oil type | Synthetic Hydrocarbons | | |
| Kinematic viscosity at 40°C | 66,5 | mm ² /s | DIN EN ISO 3104 |
| Kinematic viscosity at 100°C | 10,7 | mm ² /s | DIN EN ISO 3104 |
| Viscosity index (VI) | 151 | | DIN ISO 2909 |
| Pour point | < -50 | °C | DIN ISO 3016 |
| Flash point | > 270 | °C | DIN EN ISO 2592 |

Application

COMPGUARD MT 68 is used in compressors, particularly in reciprocating, piston and screw type compressors.

The oil change periods can be extended up to 6000 operation hours.

Packaging units

6 x 1 l bottles, 5 l canister, 20 l canister, 60 l drum, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>