



## TURMOFLUID 15 BK plus



Date of issue: 06.05.2019

**TURMOFLUID 15 BK plus** is a fully synthetic high temperature chain oil. It is suitable for non-ferrous metals and dusty environments.

### Special properties

- Excellent adhesion
- High temperature stability
- Low volatility
- Low dust binding
- Excellent corrosion and wear protection
- Very high ageing stability
- Stable to cold and hot water as well as water steam
- Suitable for nonferrous metals
- Silicone-free

Product Characteristics	Value	Dimension	Norm / Standard
Colour	orange, clear		
Density at 20°C	0,98	g/cm <sup>3</sup>	DIN 51757
Operating temperature range	-20 to 300	°C	
Oil type	Ester		
Kinematic viscosity at 40°C	65	mm <sup>2</sup> /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	9	mm <sup>2</sup> /s	DIN EN ISO 3104
Viscosity index (VI)	117		DIN ISO 2909
Pour point	< -20	°C	DIN ISO 3016
Flash point	270	°C	DIN EN ISO 2592

### Application

**TURMOFLUID 15 BK plus** is suitable for all types of chains in heated equipment, in conveyor chains e.g. in the wood industry, in driers, steamers and chains of film stretching machines.

**TURMOFLUID 15 BK plus** may be applied by oil can, drip feed oiler and automatically by pump, spray and dosing systems which are suitable for this viscosity.

### Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)  
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>