



## TURMOGREASE 2 PA EP

K P 2 P -30



Date of issue: 17.05.2018

**TURMOGREASE 2 PA EP** is a greenish/transparent soft complex soap grease for all rolling bearings and sliding bearings of the ropeway technology.

### Special properties

- High load carrying capacity
- Extremely adhesive
- Excellent corrosion protection
- Good friction and wear characteristics
- Excellent resistance to water

Product Characteristics	Value	Dimension	Norm / Standard
Colour	greenish - transparent		
Density at 20°C	0,89	g/cm <sup>3</sup>	DIN 51757
Operating temperature range	-30 to 160	°C	
Thickener	Aluminium soap		
Base oil	Mineral oil		
Kin. viscosity of the base oil at 40°C	220	mm <sup>2</sup> /s	DIN EN ISO 3104
Worked penetration	265 – 295	mm/10	DIN ISO 2137
Consistency class (NLGI)	2		DIN 51818
Dropping point	> 230	°C	DIN ISO 2176
Resistance to water	0 – 90		DIN 51807
Corrosion protection ( SKF-Emcor)	0 / 0		DIN 51802
Speed factor of grease (n x dm)	300 000	mm/min	
Four-ball test O.K. load / welded load	3800 / 4000	N	DIN 51350

### Application

For the lubrication of rolling and sliding bearings of all kinds, specially for trucks(LKW) and agricultural machines.

### Packaging units

20 x 400 g cartridges, 6 x 1 kg cans, 5 kg bucket, 25 kg hobbock, 180 kg drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)  
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>