

We have the solution...

...the future has a name



Technical Information

LUBRICANT CONSULT GMBH

Gutenbergstraße 13 · D-63477 Maintal – Germany · Telefon: +49-61 09 - 76 50-0 · Fax: +49-61 09 - 76 50-51 · Internet: www.lubcon.com

TURMOLYB SUSPENSION STR

LUBCON – High Temperature-Chain Lubricant

Description

Aqueous suspension made of synthetic oil with a special solid lubricant combination. Preferential application at high temperatures up to 450°C. A special production procedure prevents sedimentation of the solid lubricants.

Advantages

- smokeless, practically inodorous
- very good fretting reduction
- high load-carrying capacity
- good wettability
- slight formation of residues
- offers optimum corrosion protection
- high flash point of the active substance
- no irritant action on eyes or skin

Technical Data

TURMOLYB SUSPENSION STR

Colour	grey/black
Solid content	approx. 15 weight %
Density at 20°C	approx. 1,1 g/cm ³
Operating temperature range°C	+5°C up to 450°C
Flashpoint DIN EN ISO – Base oil	> 230°C
Pourpoint DIN ISO 3016	0°C

Field of Application

Due to a residue-free decomposition of the base-oil, **TURMOLYB SUSPENSION STR** is specially qualified for the application of chain-lubrication in annealing installations, furnaces and drying kilns under thermal stress.

Original Packing

10 ltr. can, 20 ltr. can, 60 ltr.drum (not returnable)

The products are subject to severe controls of manufacture and comply in full with the specifications set forth by our company. Due to the multitude of different influencing factors, we cannot assume any warranty for the successful in each case. Therefore, we recommend to perform field tests. We strictly refuse any liability.