



TURMOSYNTHGREASE AL 682

K P 2 K -20



Date of issue: 18.07.2019

TURMOSYNTHGREASE AL 682 is a light-coloured special grease for the food industry.

TURMOSYNTHGREASE AL 682 is InS H1 registered as lubricant for which an incidental contact with food technically cannot be avoided.

Special properties

- Resistant to cold/hot water
- Good adhesive properties
- Save lubrication conditions in the entire temperature range
- High load carrying capacity

Product Characteristics	Value	Dimension	Norm / Standard
Colour	colourless		
Density at 20°C	0,87	g/cm ³	DIN 51757
Operating temperature range	-25 to 120	°C	
Thickener	Aluminium complex soap		
Base oil	White oil		
Kin. viscosity of the base oil at 40°C	80	mm ² /s	DIN EN ISO 3104
Worked penetration	265 – 295	mm/10	DIN ISO 2137
Consistency class (NLGI)	2		DIN 51818
Dropping point	> 200	°C	DIN ISO 2176
Resistance to water	1 – 90		DIN 51807
Speed factor of grease (n x dm)	300 000	mm/min	

Application

Especially qualified for use in roller and friction bearings, guiding ways, sliding rails, rollers, cam disks, gear rings and toothed racks at filling and seaming machines, washing machines, conveyor plants, sorting machines, winemaking presses as well as in tubular tracks and rolling hooks in slaughter houses.

Universal grease for the application in the food and beverage industry, in the tobacco industry, in the deep-frozen food and pharmaceutical industry.

Packaging units

20 x 400 g cartridges, 6 x 1 kg cans, 25 kg hobbock, 180 kg drum



1816339



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>