



AGT-STD

High Performance Synthetic Aero-derivative Turbine Oil

Description

Castrol AGT-STD is a lubricating oil with a viscosity of 5 cSt at 100°C. It is based on high thermal stable neopentyl polyol esters, fortified with carefully selected anti-oxidant, anti-wear and anti-corrosion additives.

Application

Castrol AGT-STD is designed for use on ground gas turbines (aero-derivative) including marine and off-shore installations.

Aero-derivative gas turbines requiring a MIL-PRF-23699 G Class STD lubricant.

Meets requirements for use on the following stationary industrial gas turbines:-

- General Electric all models (LM 2500, LM 6000, LMS 100)
- Rolls-Royce / Allison / Siemens Avon, RB211, Allison 501K, Olympus, Tyne, Spey.

Advantages

When compared with other oils within the MIL-PRF-23699 G Class STD, Castrol AGT-STD: -

- low volatility at high temperature
- higher flash point than oils from competition
- excellent resistance to coking

Additional Information

When switching from one oil brand to another brand within the same specification (within the MILPRF-23699 family), the "top off" procedure is preferred. Experience has shown a gradual transition is preferred to avoid carbon shedding for elastomer seals in the lubrication circuit. For more details on compatibility, please contact your Castrol representative.

Typical Characteristics

Name	Method	Units	AGT-STD
Kinematic Viscosity @ 100°C / 212°F	ISO 9120 / ASTM D3427	mm ² /s	5.05
Kinematic Viscosity @ 40°C / 104°F	ISO 9120 / ASTM D3427	mm ² /s	25..01
Kinematic Viscosity @ -40°C / -40°F	ISO 9120 / ASTM D3427	mm ² /s	9171
Density @ 20°C / 68°F	ISO 12185 / ASTM D4052	kg/m ³	993
Viscosity stability, 72h at -40°C / -40°F, % change	FED-STD-791- 3458	%	1
Evaporation loss, 6h30mins at 204°C/ 399°F	ASTM D972	%w	3.4
Flash Point - open cup method	ISO 2592 / ASTM D92	°C/°F	269/516
Pour Point	ISO 3016 / ASTM D97	°C/°F	-57/-71
Acid Number	SAE-ARP-5088	mg KOH/g	0.2
Sediments, filtered through 1.2 micron	FED-STD-791-3010	mg/dm ³	0.3
Foam Sequence I - tendency / stability	ISO 6247 / ASTM D892	ml / ml	9/0
Foam Sequence II - tendency / stability	ISO 6247 / ASTM D892	ml / ml	5/0
Foam Sequence III - tendency / stability	ISO 6247 / ASTM D892	ml / ml	7/0
Thermal stability and corrosivity, 96h at 274°C			
Viscosity change at 40°C	FED-STD-791-3411	%	1.1
Acid number change	FED-STD-791-3411	mg KOH/g	1.3
Steel weight change	FED-STD-791-3411	mg/cm ²	0.1
Corrosion and oxidative stability 72 h at 204°C			
Viscosity change at 40°C	FED-STD-791-5308	%	16
Acid number change	FED-STD-791-5308	mg KOH/g	1.2
Steel weight change	FED-STD-791-5308	mg/cm ²	0.0
Silver weight change	FED-STD-791-5308	mg/cm ²	0.0
Aluminium weight change	FED-STD-791-5308	mg/cm ²	0.0
Magnesium weight change	FED-STD-791-5308	mg/cm ²	0.0
Copper weight change	FED-STD-791-5308	mg/cm ²	0.0
Sludge content through 10 micron	FED-STD-791-5308	mg/100 cm ³	0.0
HLPS Dynamic coking at 375°C Deposit after 20 h	SAE-ARP-5996	mg	0.6
Electrical conductivity, at 20°C	ASTM D 2624	pS/m	1500
Particle Count	NAS 1638	-	5

Subject to usual manufacturing tolerances.

AGT-STD

04 Jun 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>