

Product Data

Castrol Iloform FST X

Neat forming oil

Description

Castrol Iloform[™] FST X is a medium viscosity, chlorinated neat forming oil containing high levels of advanced lubricity and extreme pressure additives.

Application

lloform FST X has been specifically developed for the most difficult metal forming operations, such as deepdrawing, cold pilgering (inner and outer lube), fine-blanking and bending of steel and stainless steel parts.

Iloform FST X is designed to be used as received.

Advantages

- Superior adhesion and wetting properties provide homogenous lubricating film which minimises scrap rate.
- Extreme resistance to pressure and high protection against wear enables long tool and die life and thus cuts downtime and tooling costs.
- Compatible with perchloethylene degreasing application (passed DOW-cooking test).
- Excellent surface finish and cleanly sheared straight edges, especially on fine blanked components of difficult geometry and high sheet metal thickness > 10 mm.

Typical Characteristics

| | Test Method | Unit | Value |
|-----------------------------|-------------|-------|--------------|
| Appearance | Visual | - | brown liquid |
| Density at 15°C | DIN 51 757 | kg/m³ | 1140 |
| Kinematic Viscosity at 40°C | DIN 51 562 | mm³/s | 200 |
| Flash Point | ISO 2592 | °C | > 170 |

| Ester | Sulphur | Phosphorous | Chlorine | Other |
|-------|---------|-------------|----------|-------|
| ~~ | | ~~ | ~~ | × |

User Advice

Iloform FST X can be removed by using chlorinated or hydrocarbon solvents and alkaline process cleaners, the latter two also available from Castrol.

Castrol, Iloform FST, and the Castrol logo are trademarks of Castrol Limited, used under licence

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK www.castrol.com/industrial www.castrol.com/industrial

Castrol Iloform FST X Page 2 / 2