



## Enduron MT 10W-40

Diesel engine lubricant

### Description

Enduron MT is an SAE 10W-40 diesel engine lubricant formulated using unique technology.

### Application

Enduron MT is recommended particularly for MTU diesel engines where "Type 3" approval is required.

Enduron MT is also recommended for other high-speed marine engines such as MAN where ACEA E4 performance is required and/or extreme conditions require cold-start ability.

### Features / Benefits

Enduron MT uses advanced technology to increase engine endurance. Enduron MT is designed to extend oil drain intervals to the maximum and prolong engine life. As a result, high speed diesel engines benefit from reduced downtime, cost less to maintain and offer the following end-user benefits:

- Oil drain intervals extended to the maximum to reduce downtime and servicing costs.
- Engine life is increased through use of Castrol's advanced technology ensuring maximum endurance.
- Engine wear is controlled throughout the engine to reduce maintenance.
- Copes efficiently with heavy soot loading to prevent engine wear and deposits.
- Engine cleanliness is maintained by controlling deposit formation.
- Viscometrics for excellent cold-start ability.

### Approval Status

Endurong MT complies with the requirements of engine manufacturers specifying:

- ACEA E4, E5 and E7
- API CF
- MTU Oil Category 3
- Cummins CES 20072
- MAN 3277
- Volvo VDS-3

## Technical Data

Name	Method	Units	Enduron MT 10W-40
SAE Viscosity Grade	SAE J300		10W-40
Density @ 15°C	ASTM D4052	g/ml	0.866
Kinematic Viscosity @ 40°C	ASTM D445	cSt	87
Kinematic Viscosity @ 100°C	ASTM D445	cSt	13.4
Viscosity Index	ASTM D 2270		155
Base Number	ASTM D2896	mgKOH/g	16
Closed Flash Point	ASTM D93	°C	>190
Pour Point	ASTM D97	°C	-42

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

## Care and Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

## Packaging and Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Enduron MT 10W-40

14 Jun 2013

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

[www.castrolmarine.com](http://www.castrolmarine.com)